



# Xili Bearing Co., Ltd



120 mm x 180 mm x 28 mm SKF 6024 deep groove ball bearings

Bearing No. 6024

6024 Bearing 2D drawings and 3D CAD models

Size	180x120x28 mm
Bore Diameter	180 mm
Outer Diameter	120 mm
Width	28 mm
d	120 mm
D	180 mm
B	28 mm
d <sub>1</sub>	139.05 mm
D <sub>2</sub>	165.3 mm
d <sub>a</sub> - min.	129 mm
D <sub>a</sub> - max.	171 mm
r <sub>a</sub> - max.	2 mm
Basic dynamic load rating - C	88.4 kN
Basic static load rating - C <sub>0</sub>	80 kN
Fatigue load limit - P <sub>u</sub>	2.8 kN
Reference speed	7500 r/min
Limiting speed	4800 r/min
Calculation factor - k <sub>r</sub>	0.025
Calculation factor - f <sub>0</sub>	15.9
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.16



## Xili Bearing Co., Ltd

EAN	7316576621499
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	120MM Bore; 180MM Outside Diameter; 28MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	6024
Weight / LBS	4.75
Outside Diameter	7.087 Inch   180 Millimeter
Bore	4.724 Inch   120 Millimeter
Outer Race Width	1.102 Inch   28 Millimeter
bore diameter:	120 mm
static load capacity:	80 kN
outside diameter:	180 mm
precision rating:	ABEC 1 (ISO Class Normal)



## Xili Bearing Co., Ltd

overall width:	28 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	28 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	2 mm
snap ring included:	Without Snap Ring
maximum rpm:	4800 RPM
internal clearance:	C0
series:	60
dynamic load capacity:	88.4 kN
$d_1$	139.05 mm
$D_2$	165.3 mm
$r_{1,2}$ min.	2 mm
$d_a$ min.	129 mm
$D_a$ max.	171 mm
$r_a$ max.	2 mm
Basic dynamic load rating C	88.4 kN
Basic static load rating $C_0$	80 kN
Fatigue load limit $P_u$	2.75 kN
Calculation factor $k_r$	0.025
Calculation factor $f_0$	15.9
Mass bearing	2.1 kg